PATHFINDER I LED Outdoor Wall Mount

52120

- Aluminum & Glass
- 3000K Color Temperature
- Wet Location
- 120-277V input
- Photocell (PHC) and Motion Sensory (MSP) option available
- Dark Sky










Job Name: ___

Quantity : ___

Job Type : _____






PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Choose from triangular or spherical profiles as they discreetly extend from the wall. Available with a photocell option, these archetypal forms purposely blend into the architectural landscape creating safer spaces that shine light on locations of interest. Available in Black, Architectural Bronze, or Metallic Sliver

- · Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



MEASUREMENTS

DIMENSION : 5.5" W x 5.5" H x 4" Ext **BACK PLATE** : 5.5" W x 5.5" H x 2.75" HCO

HANGING WEIGHT : 2.03 lb

LAMPING

: 120-277V INPUT VOLTAGE

: 1,270 Rated (820 Del.) **LUMENS**

: 1 x 15W LED PCB Integrated, 15W Total BULB

: (Integrated) **BULB INCLUDED**

: Yes DIMMABLE : 90 CRI CRI : 3000K COLOR_TEMP

FINISHES OPTION

Architectural Bronze

Black Silver

*Photocell option available in Architectural Bronze only

MATERIAL

Aluminum, Glass

RATINGS

CETLUS Wet Location JA8 Listed ADA DARKSKY











ADDITIONAL

INSTALL UP/DOWN: UP **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online



P. 626.956.4200 | F. 626.956.4225 | maximlighting.com