COUNTERMAX MX-LD-AC I UNDERCABINET LED DISC

53830 / 53832 / 53835 / 53836

- Surfaced or Recessed installation with 30°swivel
- Available in 2700K and 3000K Color Temperature, CRI 90+
- Line Voltage Construction, no driver needed
- Aluminum heat sink
- Link up to 20 units on single power supply
- Dimmable with Triac Dimmer
- Not suitable for enclosed cabinets
- Comes individual or in packs (3 pucks)

Job Name : ___ Job Type Quantity : Comments :









PRODUCT DESCRIPTION

The versatile MX-LD-AC LED disc features two piece aluminum construction that allowing for surface mounting all recessed. They are designed for daisy chain installation of up to 20 discs on one power supply. Fully dimmable with ELV and Triac dimmers. This combination of versatility, safety, energy efficiency and dimmability make the MX-LD-AC LED discs the smart choice for disc lighting.

2.75"D x 1"H

2.75"D x 1"H

2.75"D x 1"H

2.75"D x 1"H

1 x 4W PCB LED (Integrated)

1 x 4W PCB LED (Integrated)

3 x 4W PCB LED (Integrated)

3 x 4W PCB LED (Integrated)

HANGING

WEIGHT

0.38 lb

0.38 lb

1.50 lb

1.50 lb

CRI

90+

90+

90+

90+

LUMENS

250 200

250 200

250 200

250 200

INIT. DEL

COL

3000K

2700K

3000K

2700K

TEMP. DIMMABLE INPUT

Triac CL

Triac CL

Triac CL

Triac CL

120V

120V

120V

120V

MEASUREMENTS

53830

53832

*53835

*53836

53830

53832

*53835

*53836

LAMPING

MODEL BULB TYPE

MODEL DISC DIMENSION

1

1

3

3

*Kit required (sold separately)



\frown	



Two piece Aluminum Construction for both Surface and Recessed Installation



53885 BK, WT 72" Power Cord

53886 BK, WT 12" Connecting Cord



24" Connecting Cord Junction Box 4"L x 2.5"W x 1"H

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

FINISHES: BRON7E (B7)

SATIN NICKEL (SN)	
WHITE (WT)	

MATERIAL Aluminum

RATINGS ETL/cETL Dry Location Dimmable



ADDITIONAL:

ROTATION RATED LIFE OPERATING TEMP PHOTOMETRIC

: 30° SWIVEL : 35,000 Hours : -20° C (-4°), 40°C (104°F) : Report Found Online