VAPORTIGHT | 48" FLUSH MOUNT

57535WTDG

- Dark Gray finish with PMMA Frosted Lens
- IP65 Wet Location
- Beam Angle: 130°
- Non-Corrosive Plastic injection housing and Stainless Steel mounting clips
- Clip-in design requires no tools
- Vandal Proof or Harsh Weather
- Wattage Selectable: 30 | 40 | 50W
- 5CCT Selectable: 27-30-35-40-50
- 120-277V, 0-10V
- cETLus Certified
- DLC Premium Listed
- NSF Rated
- Approved for CA T24
- FCC CFR 47 GCC Part 15, Subpart B:2017 Dimmable

Job Name	
Job Type	
Quantity	
Comments	

PRODUCT DESCRIPTION

The Vapor Tight light fixture is constructed for any environment. With an integrated 4CCT Select switch, toggle between 3000-5000k. Not just CCT Selectable, this model features a wattage selectable switch allowing you to control the brightness of a space and its electrical usage. Ideal for commercial and industrial applications such as garage facilities and stairwells, this product is both vandal proof and constructed for installation in harsher climates



MEASUREMEN	TS
------------	----

DIMENSIONS : 48"L x 4.5"W x 3.5"H WEIGHT : 2.7 LB

LAMPING

INPUT VOLTAGE WATTAGE LUMENS COLOR TEMP DIMMABLE : 120-277V : 50 | 40 | 30W (SELECTABLE) : 6500 | 52000 | 3900 : 2700-3000-3500-4000-5000 : 0-10V FINISHES OPTION

White (WT)

MATERIAL

Plastic Injection Housing Metal Heat Sink Stainless Steel Mounting Clips PMMA Frosted Lens

CERTIFICATIONS

cETLus DLC Premium Listed NSF Rated Approved for CA T24 FCC CFR 47 GCC Part 15, Subpart B:2017



RATED LIFE Average life (L70) of 50,000 hours

OPERATING TEMPERATURE

-40° - 122° F

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com