# WAFER LED I SURFACE MOUNT

## 57710 / 57712 / 57714 / 57780 / 57784

- Die Cast Aluminum
- . Size options between 5", 7" and 10"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Bronze (BZ), Black (BK), and Satin Nickel (SN)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor
- and above showers • ETL/cETL IP65







57780WT Empty Shell for 7" Round Wafer







## **PRODUCT DESCRIPTION**

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.

Installs into 3.25" and 4" electrical box with a minimum 2.5" depth



## **MEASUREMENTS**

MODEL	DIMENSION
57710	5"D x 0.5"H
57712	7"D x 0.5"H
57780	7"D x 1.25"H
57784	7"D x 1.75"H
57714	10"D x 0.5"H

## LAMPING

1

ļ

ļ

ļ

MODEL	BULB TYPE
*57710	10W LED (Integrated)
*57712	15W LED (Integrated)
*57780	Add on shell
*57784	15W LED (Integrated)
*57714	20W LED (Integrated)

HANGING WEIGHT			
0.88 lb			
1.21 lb			

1.75 lb

7710	10W LED (Integrated)
7712	15W LED (Integrated)
7780	Add on shell
7784	15W LED (Integrated)
7714	20W LED (Integrated)

IANGING VEIGHT		
.88 lb .21 lb		

### LUMENS COL CRI INIT DEL TEMP. DIMMABLE INPUT 3000K ELV 120V 90+700 600 90+ 1050 900 3000K ELV 120V 3000K ELV 120V 90+ 1100 900 90+ 1400 1200 3000K ELV 120V

\*120-277V input and 0-10V dimming available upon request

Always consult a qualified electrician before installing any lighting product



## WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

### EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com







MATERIAL: Die Cast Aluminum PMMA Acrylic Diffuser

**AVAILABLE SIZES:** 5" | 7" | 10"

## **RATINGS:**

ETL/CETL IP65 Wet Location Energy Star Title 24 JA8 compliant ADA Dimmable Closets Rated: 410.8 & 410.16 ((Tb)

## ADDITIONAL:

RATED LIFE: 50,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online