

# WAFER LED 15" I SURFACE MOUNT

## 57736


- Edge-Lit Technology, evenly distributed light
- Available in 3000K color temperature (See 57737 for 4000K)
- Available in Bronze (BZ), Satin Nickel (SN), and White (WT)
- Dimmable with ELV dimmer at 120V
- 120-277 Input Voltage
- Energy Star listed
- Easy to install: Fits 4" Outlet Box (Pancake NOT recommended)
- Approved for use in closets and storage spaces
- Suitable for Wet location
- ETL/cETL IP65

Job Name : \_\_\_\_\_  
Job Type : \_\_\_\_\_  
Quantity : \_\_\_\_\_  
Comments : \_\_\_\_\_



### PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



### MEASUREMENTS

DIMENSIONS : 15"L x 15"W x 0.5"H  
HANGING WEIGHT : 3.53 lb      MAX OH : 0.5"  
HCO : 0.5"      MIN OH : 0.5"  
BP Width : 4.1"

### LAMPING

INPUT VOLTAGE : 120-277V  
LUMENS : 2500 Rated (2200 Del.)  
BULB : (1) 36W PCB LED (Integrated)  
DIMMABLE : Dimmable with ELV Dimmer at 120V  
CRI : 90+  
COLOR TEMPERATURE: 3000K

### FINISHES OPTIONS:

White (WT)  
Bronze (BZ)  
Satin Nickel (SN)



### MATERIAL:

Aluminum  
PMMA Acrylic Diffuser

### RATINGS:

ETL/cETL IP65  
Wet Location  
Energy Star  
J8 Title 24



### ADDITIONAL:

RATED LIFE: 40,000 Hours  
OPERATING TEMP: -20° C (-4°), 40° C (104° F)  
PHOTOMETRIC: Report Found Online

*Always consult a qualified electrician before installing any lighting product*



**WESTERN DISTRIBUTION CENTER (HEADQUARTER)**  
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

**EASTERN DISTRIBUTION CENTER**  
4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com