COVE I Recessed Downlight

57792 / 57793 /57794 / 57796 / 57797 / 57798

- LED 3000K or 4000K Options
- 4 inch and 6 inch Recessed Can Substitute
- UL Outlet Box fitted on fixture
- Dimmable with Triac Dimmer
- · Good for new construction and remodels
- Suitable for closets according to NEC Section 410.8 & 410.16
- Indirect lighting into cove for soft-even illumination
- IC-Rated for direct contact with insulation
- Damp Location Rated
- Title 24
- ETL/cETL
- CRI 90+





57790 Cove Rough in Plate for New Construction (Hanging weight: 10lb)

PRODUCT DESCRIPTION

Maxim's Cove recessed downlight series offers an IC Airtight UL rated Outlet Box that is fitted to the fixture for easy installation without the use of a recessed housing. To reduce glare that is associated with other recessed downlights, the Cove uses an innovative concave lens that directs the light upward and is then reflected back down offering even and abundant illumination. The Cove is one of the most versatile downlights in the market.

AAEA SIIDEAAENITS

LAMPING



MODEL	DIMENSION	BP HEIGHT	нсо	HANGING WEIGHT
57792	4.75"D x 3.25"H	1.85"H	3.30"	0.55 lb
57793	4.75"D x 3.25"H	1.85"H	3.30"	0.55 lb
57794	4.75"D x 3.25"H	1.85"H	3.30"	0.55 lb
57796	6.75"D x 3.75"H	1.85"H	3.80"	0.77 lb
57797	6.75"D x 3.75"H	1.85"H	3.30"	0.77 lb
57798	6.75"D x 3.75"H	1.85"H	3.80"	0.77 lb

LAMPING				COL			
MODEL	BULB TYPE	CRI	LUMENS		DIMMABLE	INPUT	
57792 57793 57794 57796 57797 57798	12K D7 6 @98 flbh/ [fUH/XŁ 12W PCB LED (integrated) 9W PCB LED (integrated) 12W PCB LED (integrated) 15K D7 6 @98 flntegratedŁ 15K D7 6 @98 flntegratedŁ	90+ 90+ 90+ 90+ 90+ 90+	620 620 540 720 950 950	3000K 4000K 3000K 3000K 3000K 4000K	Triac CL Triac CL Triac CL Triac CL Triac CL Triac CL	120V 120V 120V 120V 120V 120V 120V	

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

FINISHES OPTIONS:

White (WT)

MATERIAL:

Aluminum

AVAILABLE SIZES:

4" | 6"

RATINGS: FTL/CFTL

IC Airtight Damp Location Energy Star Title 24 Closets Rated: NEC 410.8 & 410.16



ADDITIONAL:

RATED LIFE: 40,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) PHOTOMETRIC: Report Found Online LIGHTING DIRECTION: Down



Quantity :

Comments :