SOLSTICE I CHANDELIER W/FAN 60006SN

- FTL/CETL
- Title 20 listed
- LED 3000K
- Suitable for Dry location
- Wall mountable (remote control included)

Job Name	:	
Job Type	:	
Quantity	:	
Comments	:	



ACCESSORIES (Sold Separately)



FCT6000WT Wall Control

PRODUCT DESCRIPTION

The Solstice Chandelier with Fan houses three innovatively curved fan blades within a cage of artfully bent Satin Nickel channel to create a classic form in light. Its architecturally contemporary styling is paired with high-powered LED lighting making it functional and fantastic for transitional and modern settings.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



MEASUREMENTS DIMENSIONS : 34.25"D x 23.5"H HANGING WEIGHT : 8.19 lb BLADE : 3 Blades with 22" span **BLADE PITCH** : Varying BLADE TO CEILING : 14"H

LAMPING

CRI

INPUT VOLTAGE :120V LUMENS : 5200 BULB : (8) 7W PCB LED (Integrated), 56W Total DIMMABLE : Yes :80+ COLOR TEMP : 3000K MOTOR TYPE : DC Motor

AIRFLOW SPEEDS :6 AIRFLOW CFM : 5057 ELECTRICITY USE · 31 90W AIRFLOW EFFICIENCY: 158.5

FINISHES OPTIONS:

Satin Nickel

MATERIAL:

Steel Polypropelene Fan Blades Aluminum

INCLUDES

• Wall Mountable Remote Control

1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118SN)
- 24" (FRD0124SN)
- 30" (FRD0130SN) • 36" (FRD0136SN)

RATINGS:

ETL CETL Dry Location Title 20



ADDITIONAL: RATED LIFE: 35,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F) LIGHTING DIRECTION: Up



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com