

COUNTERMAX MX-L-24-SS | 24V SLIM STICK

89800 | 89801 | 89802 | 89803 | 89804

- Aluminum finish with Black accessories
- Even distribution of LED diffused through opal white lens
- 24V system must be paired with driver accessories
- Linkable end-to-end or with MX Interlink cord
- Adjustable mounting clips allow for angled installation
- Dimmable with LED dimmers and Touch dimmer Energy Star Certified
- Title 24 JA8 listed=
- 3000K Color Temperature
- CRI 90+

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____




• Includes adjustable mounting clips




PRODUCT DESCRIPTION

Narrow Aluminum channels of LED are easily concealed in an economical way to tackle your task lighting. Installation is simple with an adjustable bracket that allows you to direct the light to where you need it, and a simple plug-in or hard wire power supply. Available in lengths from 6" to 48" and varies accessories, Slim Stick is the easy solution for your task lighting installation.

LED PROFILE



IN-LINE DIMMER



FINISHES:

ALUMINUM (AL) 

MATERIAL

Aluminum

RATINGS

cETLus
 Dry Location
 Energy Star
 JA8 Listed



ADDITIONAL

OPERATING TEMPERATURE: -20°
 C (-4°F), 40°C (104°F)

MEASUREMENTS

LAMPING

MODEL	DIMENSION	BULB TYPE	COLOR TEMP	CRI	LUMENS		DIMMABLE	V INPUT
					RATED	DELIVERED		
89800	0.75"W x 0.5"H x 6"L	3W Integrated LED	3000K	90+	350	195	LED	24V
89801	0.75"W x 0.5"H x 12"L	5W Integrated LED	3000K	90+	700	395	LED	24V
89802	0.75"W x 0.5"H x 24"L	10W Integrated LED	3000K	90+	1050	780	LED	24V
89803	0.75"W x 0.5"H x 36"L	15W Integrated LED	3000K	90+	1400	1170	LED	24V
89804	0.75"W x 0.5"H x 48"L	20W Integrated LED	3000K	90+	1750	1560	LED	24V

(SEE COMPATIBLE DRIVERS AND ACCESSORIES ON NEXT PAGE FOR DIMMING INFORMATION)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746
EASTERN DISTRIBUTION CENTER
 101 GARDNER PARK | PEACHTREE CITY, GA 30269
 P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

24V CONSTANT VOLTAGE LED DRIVERS


Hard Wired Power Supplies



Hard Wired Driver

DHW898-2496BK
W8.5" H3.25"

100-295V input
96W MAX
Includes Plug in Connector
Compatible with Triac or ELV



Dimmable Driver Switch

SWT898-2460WT
60W MAX
SWT898-2475WT
75W MAX
2"W x 2.25"L x 4.25"H

Plug-in Power Supplies

*can be used with in-line dimmer switch



89811BK
24W Plug-In Driver Non-dimming



DRV898-2460BK (89812BK)
60W Plug-In Driver Non-Dimming



89814BK
96W Plug-In Driver Non Dimming



89835AL
In-Line Dimmer Switch
On/Off and Brightness Control

CONNECTING CORDS



89822BK 12"
*includes
ON/OFF switch



CRD898-18BK
18"



CRD898-36BK
36"



CRD898-60BK
60"



89833BK
LOW VOLTAGE SPLICE BOX
L 1.75" x W 2.25" x H 0.5"



90° CONNECTOR
89830BK
L



89831BK
R

Always consult a qualified electrician before installing any lighting product.