
Job Type:_



PRODUCT DESCRIPTION

Rods of bubble glass are encased inside a Clear glass cylinder, which are supported in a cast Polished Chrome frame. Dual LED modules bring the bubble glass to life, while also providing ample illumination to the surface below.



MEASUREMENTS

HANGING WEIGHT

DIMENSION

MAX OAH

CANOPY

LAMPING

LUMENS

DIMMABLE

BULB

CRI

: 35.25" L x 11.5" W x 7" H : 64.5" OAH : 5.25" W x 1" H x 15.6" L : 24.2 lb INPUT VOLTAGE : 120V

: 4,160 Rated (2,050 Del.) : 16 x 4.5W LED PCB Integrated , 72W Total BULB INCLUDED : (Integrated) : Triac CL : 80+ CRI COLOR_TEMP : 3000K

FINISHES OPTION

Polished Chrome (PC)

GLASS Clear CL

MATERIAL Metal, Glass

RATINGS cETLus Dry Location



ADDITIONAL OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com