
Quantity:



PRODUCT DESCRIPTION

Commercial grade energy efficient lighting featuring linear frames of metal finished in Satin Nickel diffused by an etched opal acrylic creating an updated energy efficient classic.



MEASUREMENTS

DIMENSION		:
MAX OAH		:
HANGING WEIGHT		:
LAMPING		
INPUT VOLTAGE	:	12
lumens	:	9
BULB	:	1
BULB INCLUDED	:	(Ir
DIMMABLE	:	N
CRI	:	90
COLOR_TEMP	:	30
LIGHTING_DIRECTION	:	UI

7" W x 10" H x 3.5" Ext 4.25" W x 9.75" H 1.85 lb

G OLTAGE : 120-277V ; : 950 Rated : 1 x 15W LED PCB Integrated , 15W Total CLUDED : (Integrated) BLE : No : 90+ CRI _TEMP : 3000K G DIRECTION : UP

FINISHES OPTION

Satin Nickel (SN)

GLASS White WT

MATERIAL Steel, Opal Acrylic

RATINGS CETLus Damp Location ADA



ADDITIONAL

INSTALL UP/DOWN: Up RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com